MENNEKES
MY POWER CONNECTION

# Wall mounted socket

Part no. 1144A

- screw terminals
- X-CONTACT®
- suitable for through wiring
- internal fixing
- enclosure base can be turned 180°
- with 6 fixing points to accommodate special terminals
- products with pilot contacts on request

## Technical specifications

| | |
|---|---|
| Ampere | 63 A |
| Poles | 5 p |
| Voltage | 230 V |
| Clock position | 9 h |
| Hertz | 50-60 Hz |
| Connection technology | Screw terminals |
| Contact | X-CONTACT |
| Protection type | IP44 |
| Weight | 925 g |
| Certifications | VDE |

## Drawing




| Drawing | Amp. | 63 | | |
|---|---|---|---|---|
| 1 MB 213 | Poles | 3 | 4 | 5 |
| Dim. in mm | a | 170 | 170 | 170 |
| | b | 118 | 118 | 118 |
| | c | 164 | 164 | 164 |
| | d | 134.5 | 134.5 | 134.5 |
| | e | 103 | 103 | 103 |
| | f | 6.1 | 6.1 | 6.1 |
| | g. | 6 | 6 | 6 |
| | h | 216 | 216 | 216 |
| | M | 40 | 40 | 40 |
| | M* | 2xM40 (blind) to be cut out | | |
| Max. cable diam. (mm) | | 32 | 32 | 32 |
| Terminal for cond. cross section (mm²) min.-max. | | —25 | —25 | —25 |


Subject to modificat. No liability for misprints.